



VANDAL RESISTANT

# RHINO 66

SERIES

# IQL



LINKABLE  
NON-FLICKER

## VANDAL & IMPACT RESISTANT LED BATTEN



## TECHNICAL

Body	Aluminium, Polycarbonate diffuser
Colour Temperature	5000K ( also available in NSP Amber* options )
Average LED and Control Gear Life	>78,000 hrs (L70/Ta25c)
Beam Angle	120° degrees
Efficacy	130 Lm/w
CRI	> 80
Max Junction Temperature	150C
Cooling	Conduction, Convection
Operating Range Tc	-35°C – 50°C
Thermal Management	Aluminium Heatsink



## ELECTRICAL

Power Supply	Non-Flicker LED Driver
Protection	Over Voltage, Short Circuit and Over Temperature
Power Factor	> 0.96
Total Harmonic Distortion (THD)	<15%
Ingress Protection Rating	IP66
Impact Rating	IK10
Certification	RCM, EMC, CE,
Warranty	3 Years



## ORDER CODES

Model	Wattage	Light Colour	Lumens	Weight	Size (in mm)		
					A	B	C
RWP66-600	20 watts	5000K	2,600Lm	1.9kg	600	83	63
RWP66-600-MS	20 watts	5000K	2,600Lm	1.9kg	600	83	63
RWP66-1200	40 watts	5000K	5,200Lm	3.3kg	1200	83	63
RWP66-1200-MS	40 watts	5000K	5,200Lm	3.3kg	1200	83	63

## ACCESSORIES

RWP66-ANGCLIP	Adjustable Angle Change Clip
RWP66-BR	45 Degree Metal Bracket
RWP66-SUSCAB	Suspending Steel Cable 1m Length

Technical Data sheets available on request. Model appearance may vary.  
July 2020 specifications are subject to change without prior notice.



**SMARTER LIGHTING SOLUTIONS**  
**IQL Australia**  
 6/24 Yalgar Rd, Kirrawee NSW 2232  
 www.iqlighting.com.au  
 1300 475 444



\*NatureSpec wildlife safe amber light available on request