

# BURST RGBW

COMMERCIAL

# IQL



**ARCHITECTURAL AND  
FEATURE LIGHTING**



## TECHNICAL

<b>Light Source</b>	Lumiled
<b>Body</b>	Aluminium Alloy
<b>Colour Temperature:</b>	RGBW (W = 4000K)
<b>Average LED &amp; Control Gear Life Projection</b>	>50000hrs L70
<b>Beam Angle:</b>	30/60/90/120°
<b>Efficacy:</b>	150Lm/W = 4000K
<b>CRI:</b>	Ra70
<b>Mounting Options</b>	Bracket Mount
<b>Housing Colour</b>	White

## ELECTRICAL

<b>Wattage</b>	80W - 300W
<b>Power Supply</b>	100-277VAC
<b>Control:</b>	DMX 512
<b>Protection:</b>	6kV line-earth, 4kV line-line
<b>Power Factor:</b>	>.93
<b>Ingress Protection Rating</b>	IP67
<b>Impact Rating</b>	IK10
<b>Certification</b>	RCM

## KEY FEATURES

High Quality LED chips and Driver

Multiple beam angles available

Epoxy anti-corrosion coating

## ORDER CODES

Model	CCT	Lumens	DIMENSIONS (MM)	Weight
<b>BUR80</b>	White = 4000K	12000 (WH)	450 390 170	5.6kg
<b>BUR100</b>	White = 4000K	15000 (WH)	450 390 170	5.6kg
<b>BUR120</b>	White = 4000K	18000 (WH)	485 460 170	8kg
<b>BUR200</b>	White = 4000K	30000 (WH)	595 460 170	10.8kg
<b>BUR300</b>	White = 4000K	45000 (WH)	590 480 223	12.5kg



Technical Data sheets available on request. Model appearance may vary. | March 2025 specifications are subject to change without prior notice.