

ESTATE 21 SERIES

COMMERCIAL

IQL



***STREET LIGHT, URBAN ROAD
CAR PARK, PATHWAY, PARK***



TECHNICAL

Light Source	Lumiled
Body	Aluminium Alloy
Colour Temperature:	4000K (5000K option)
Average LED & Control Gear Life Projection	>50000Hrs L70
Beam Angle:	Type IV
Efficacy:	150Lm/W
CRI:	Ra70
Mounting Options	38mm side entry mount
Housing Colour	Brunswick Green (other colours on request)

ELECTRICAL

Wattage	21W 45W
Power Supply Constant Current	Inventronics
Protection:	6kV line-earth, 4kV line-line
Power Factor:	> 0.95
Ingress Protection Rating	IP65
Impact Rating	IK08
Certification	AS/NZS 60598.1 AS/NZS 60598.2.3 AS CISPR 15

ORDER CODES

Model	CCT	Lumens	DIMENSIONS (MM)	Weight
IQL-ESTATE 21	4000K	3150LM	Diameter 55mm - 21mm high	3.85 kg
IQL-ESTATE 45	4000K	6750LM	Diameter 55mm - 21mm high	3.85 kg

KEY FEATURES

- Two wattages available
- System efficiency up to 150Lm/w, lumen package



*NatureSpec wildlife safe amber light available on request

Technical Data sheets available on request. Model appearance may vary. | March 2025 specifications are subject to change without prior notice.