

**STRAND**  
COMMERCIAL

**IQL**



***PARK  
PATHWAY  
LANDSCAPE***



## TECHNICAL

Light Source	Cree
Body	Aluminium
Diffuser	Honeycomb
Trim	SS316
Colour Temperature:	3000K/4000K/5000K
Average LED & Control Gear Life Projection	>100000hrs L70
Beam Angle:	Available on request
Efficacy:	80 Lm/W
CRI:	>80

## ORDER CODES

Model	CCT	Lumens	DIMENSIONS (MM)	Weight
STS-7W-HC-3K	3000K	490Lm	130 diameter	1.5kg
STS-7W-HC-3K-24VDC	3000K	490Lm	130 diameter	2kg
STS-11-HC-3K	3000K	770Lm	130 diameter	1.5kg
STS-16W-5K	5000K	1120Lm	130 diameter	2kg
STS-16W-5K-24VDC	5000K	1120Lm	130 diameter	3.1kg
STS-160MM-TRIM	SS316		130 diameter	1.8kg
STS-250MM-TRIM	SS316		130 diameter	3.1kg

## ELECTRICAL

Wattage	7W 11W 16W
Power Supply Constant Current	100-240 VAC (Meanwell) and 24VDC
Control:	On Request
Power Factor:	> 0.9
Ingress Protection Rating	IP67
Impact Rating	IK08
Certification	RCM

## KEY FEATURES

- Recessed Up
- Tilt Option Available



Technical Data sheets available on request. Model appearance may vary. | March 2025 specifications are subject to change without prior notice.