

CORSA II
SERIES

IQL



**COMMERCIAL CANOPY
LED LOW BAY**



TECHNICAL

Light Source	Lumiled
Body	Aluminium
Colour Temperature	5700K (also available in 4000K on request)
Average LED and Control Gear Life	>50,000 hrs
Beam Angle	120° degrees (Symmetrical)
Efficacy	130 Lm/w
CRI	> 70
Max Junction Temperature	150°C
Thermal Management	Aluminium Heatsink
Cooling	Conduction, Convection
Operating Range Tc	-35°C to 55°C

ELECTRICAL

Power Supply	Sosen
Protection	Over Voltage, Short Circuit and Over Temperature
Power Factor	> 0.95
Ingress Protection Rating	IP65
Impact Rating	IK08 (also available in IK10 Polycarbonate lens on request)
Certification	RCM

KEY FEATURES

- High Quality Construction
- Phillips Lumileds LED chips
- High Lumen Output 130 Lm/W
- IP65 Protected against water exposure


ACCESSORIES

- COR-RC** Recessed Canopy Plate - Custom sizes available



ORDER CODES

Model	Wattage	Light Colour	Lumens	Weight	Size (in mm)		
					A	B	C
COR-75	75 watts	Cool White 5000k	9,750Lm	4.8kg	420	420	100
COR-110	110 watts	Cool White 5000k	14,300Lm	5.1kg	420	420	100
COR-150	150 watts	Cool White 5000k	19,500Lm	5.1kg	420	420	100



Technical Data sheets available on request. Model appearance may vary. | March 2025 specifications are subject to change without prior notice.