

# PARKLAND

SERIES

# IQL



***PARKLAND,  
PRIVATE AND PUBLIC LANDSCAPE,  
PATHWAY AND AREA LIGHTING***



## TECHNICAL

<b>Light Source</b>	Lumiled
<b>Body</b>	Die Cast Aluminium Alloy
<b>Body Colour</b>	Black
<b>Fasteners</b>	Stainless Steel
<b>Colour Temperature:</b>	4000K (3000K, 5000K and Amber NSP optional)
<b>Average LED &amp; Control Gear Life Projection</b>	L70 @ 100000hrs
<b>Beam Angle:</b>	Type V
<b>Efficacy:</b>	120LmW
<b>CRI:</b>	Ra70 (Ra80 optional)
<b>Lumen output:</b>	4800Lm - 12000Lm

## ELECTRICAL

<b>Power Supply Constant Current</b>	Inventronics 100-277Vac (347-480Vac option )
<b>Dimming Options</b>	0-10v / PMW / Timer / DALI
<b>Protection:</b>	6kV Line-Line, 10kV Line-Earth (10Kv & 20Kv SPD available)
<b>Power Factor:</b>	> 0.9
<b>Ingress Protection Rating</b>	IP66
<b>Impact Rating</b>	IK08
<b>Certification</b>	RCM

## ORDER CODES

MODEL	CCT	LUMEN	DIMENSIONS (MM)	WEIGHT
PAR-40	4000K	4800Lm	51 x 51 x 64	7kg
PAR-60	4000K	7200Lm	51 x 51 x 64	7kg
PAR-75	4000K	9000Lm	51 x 51 x 64	7kg
PAR-100	4000K	12,000Lm	51 x 51 x 64	7kg

## KEY FEATURES

LED Post Top Light/Park/Pathway/Landscape
Contemporary, architectural design, elegant appearance
Smooth housing without any exposed screws
Lumen Packages ranging from 4800-12000lm
100-277V 50/60Hz, 277-480V Available
Professional optic provide an excellent effect, managing glare while providing high levels of visibility
60mm & 76mm mount available
Area, site and pedestrian scale applications



\*NatureSpec wildlife safe amber light available on request

Technical Data sheets available on request. Model appearance may vary. | March 2025 specifications are subject to change without prior notice.