

ZENVO SHOOTER 480W

PRECISION LED FLOOD LIGHTING



**HEAVY DUTY INDUSTRIAL
FLOOD LIGHTING**





TECHNICAL

Light Source	Lumiled
Body	High Pressure Die-Cast Aluminium
Colour Temperature	5700K (3000, 4000K, 5000K available)
Average LED and Control Gear Life	>100,000 hrs L70
Beam Angle	Asymmetrical and symmetrical
Efficacy	145 Lm/w
CRI	> 70 standard with > 80 available on request
Max Junction Temperature	150°C
Cooling	Conduction, Convection
Operating Range	-30°C to +65°C
Operating Humidity	< 95% relative humidity
Thermal Management	Aluminium Heatsink

ELECTRICAL

Power Supply	Inventronics
Voltage	230VAC, 415VAC
Input Surge Protection	6 kV line-line, 10 kV line-earth
All-Around Protection	OVP, SCP, OTP
Protection	Waterproof (IP67) and UL Dry / Damp / Wet Location
Ingress Protection Rating	IP66
Impact Rating	IK09
Safety	SELV Output

ORDER CODES

Model	Wattage	Light Colour	Lumens*	Weight*	Size (in mm)		
					A	B	C
ZEN480	480 watts	See above	69,600	9.0kg	600	300	200

"x" in the model number denotes beam angle - 15 / 24 / 40 / 60 / 100 or Asymmetrical
 *Weights are quoted without drivers.

Technical Data sheets available on request. Model appearance may vary. | March 2025 specifications are subject to change without prior notice.

KEY FEATURES

Designed and made in Australia - Built by Australians for Australian conditions.
 Powerful 480w LED Light Engine 69,600lm

INSTALLATION

Rec. Mounting Height 8-12m



*NatureSpec wildlife safe
 amber light available on request