

AQUARIUS WALL PACK

IQL



***SECURITY, PATHWAY AND
PERIMETER LIGHTING
BUILDING FACADES***



TECHNICAL

Light Source	Lumiled
Body	Silver Cast-Aluminium
Body Colour	Silver
Fasteners	Stainless Steel
Colour Temperature:	4000K (3000K, 5000K, Amber NS options),
Average LED & Control Gear Life Projection	L80 >90,000hrs
BeamAngle:	Type III
Efficacy:	125Lm
CRI:	Ra70
Lumen output:	1550Lm-4650Lm

ELECTRICAL

Dimming Options	Available on Request
Voltage	240VAC, 12VDC
Protection:	1KV line-line, 2KV line-earth
Power Factor:	> 0.9
Ingress Protection Rating	IP66
Impact Rating	IK08
Certification	RCM

ORDER CODES

MODEL	CCT	LUMEN	DIMENSIONS (MM)	WEIGHT
AQUARIUS-WALLPK-30W	4000K	30W 3750Lm	196 x 96 x 186	2kg
AQUARIUS-WALLPK-10-12VDC	4000K	10-12VDC 1250Lm	196 x 96 x 186	2kg

KEY FEATURES

- Silver Cast Aluminium fixture is durable
- High Lumen Output
- Special desinged PC optics lens (Type III Distribution)
- For security/pathway and perimeter lighting/building facades



*NatureSpec wildlife safe amber light available on request

Technical Data sheets available on request. Model appearance may vary. | January 2026 specifications are subject to change without prior notice.