

KOMO SOLAR

SOLAR BOLLARD

VANDAL OPTION
AVAILABLE

IQL



**GARDENS, PATHWAYS,
BUILDING ENTRANCE**





TECHNICAL

Battery	LiFePO4 Battery
Body	Aluminium Alloy
Body Colour	Black
Fasteners	Stainless Steel
Colour Temperature:	3000K (4000K, 5000K and Amber NS option)
Charging Time:	6-8hrs
Beam Angle:	Type V
Efficacy:	105Lm
CRI:	Ra80
Lumen output:	420Lm

ELECTRICAL

Operating Time	Normal mode > 11 hours, intelligent mode 2-3 days
Ingress Protection Rating	IP66
Impact Rating	IK07
Certification	RCM

KEY FEATURES

- Unique and modern appearance
- Visor is available as accessory for shield lighting
- Professional Type IV/Type V light distribution
- High efficient Mono-crystalline solar panel
- Long lifespan LiFePO4 battery, 8-hour charging, working 2-3 days
- Rag bolt assembly included

ORDER CODES

MODEL	CCT	LUMEN	DIMENSIONS (MM)	WEIGHT
MSCB-420	3000K	420Lm	106 x 21 x 21	6.6kg
MSCB-Remote				
MSCB-Visor				



Technical Data sheets available on request. Model appearance may vary. | January 2026 specifications are subject to change without prior notice.



*NatureSpec wildlife safe amber light available on request