

KOMO BOLLARD

PLUS COASTAL SERIES



**GARDENS
PATHWAYS**



*OPTIONS AVAILABLE



TECHNICAL

| | |
|---|--|
| Light Source | Lumiled |
| Body | Aluminium Alloy |
| Body Colour | Black (Silver or White options) |
| Fasteners | Stainless Steel |
| Colour Temperature: | 4000K (3000K, 5000K NatureSpec optional) |
| Average LED & Control Gear Life Projection | L80 >90,000hrs |
| Beam Angle: | Type V (Type IV Option) |
| Efficacy: | 85Lm |
| CRI: | Ra80 |
| Lumen output: | 2040Lm |

ELECTRICAL

| | |
|----------------------------------|---|
| Dimming Options | Available on Request |
| Voltage | 240VAC (ELV on request) |
| Protection: | 0.5KV line-line, 2KV line earth/ 1KV line-line, 2KV Line-earth |
| Power Factor: | > 0.9 |
| Ingress Protection Rating | IP66 |
| Impact Rating | IK10 |
| Certification | RCM |

KEY FEATURES

Unique and modern appearance

Visor is available as accessory for shield lighting

Professional Type IV/Type V light distribution

ORDER CODES

| ORDER CODES | CCT | LUMENS | DIMENSIONS | WEIGHT |
|---------------|-------|--------|------------|--------|
| KOMO24-900 | 4000K | 2040Lm | 920 x 160 | 6KG |
| KOMO24-900-AU | 4000K | 2040Lm | 920 x 160 | 6KG |
| KOMO24-GS | | | | |



*NatureSpec wildlife safe amber light available on request

Technical Data sheets available on request. Model appearance may vary. | January 2026 specifications are subject to change without prior notice.