

SATELLITE HT LOW GLARE

COMMERCIAL/INDUSTRIAL

IQL



***UP TO 70°C CONTINUAL RUN
WORKSHOP
WAREHOUSE
INDUSTRIAL USE***



TECHNICAL

Light Source	Lumiled
Body	Aluminium Alloy
Colour Temperature:	5000K (3000K, 4000k Optional)
Average LED & Control Gear Life Projection	>164000hrs L70
Beam Angle:	60Degree/120 Degree
Efficacy:	160 Lm/W
CRI:	Ra70
Mounting Options	Suspension Mount/Bracket Mount
Housing Colour	Black

ELECTRICAL

Wattage	200W
Power Supply	Inventronics
Dimming Options	Dali
Protection:	6kV line-line, 20kv line-earth
Power Factor:	>0.92
Ingress Protection Rating	IP65
Impact Rating	IK08
Certification	RCM

ORDER CODES

Model	CCT	Lumens	DIMENSIONS (MM)	Weight
SAT200HT-19UGR SAT200- HT	5000K	32000Lm	455 455 360	7.89kg

KEY FEATURES

Cold-forge heat sink with excellent heat dissipation while keep the lamps in smaller size



Technical Data sheets available on request. Model appearance may vary. | January 2026 specifications are subject to change without prior notice.