

# XTREME LX G3

QUICK FIT  
BRACKET

# IQL



**FLOOD LIGHT,  
CCT & POWER CHANGE**



## TECHNICAL

<b>Light Source</b>	Lumiled
<b>Body</b>	Die-cast aluminium
<b>Colour Temperature:</b>	2700/4000/5700 - colour change
<b>Average LED &amp; Control Gear Life Projection</b>	L70 > 85000hrs
<b>Beam Angle:</b>	Assymetrical
<b>Efficacy:</b>	160Lm @ 4000K
<b>CRI:</b>	>80
<b>Mounting Options</b>	Trunion Bracket
<b>Housing Colour</b>	Black

## KEY FEATURES

- High Impact Protection IK11+
- Colour Change
- Power Change
- UV Stabilised Powder Coating
- Angle Bracket for Easy Installation

## ELECTRICAL

<b>Wattage</b>	30W-300W
<b>Power Supply Constant Current</b>	108vac ~ 305vac >100,00hrs
<b>Dimming Options</b>	Non-dimmable (dimming options available)
<b>Protection:</b>	Over Voltage, Short Circuit and Over Temperature
<b>Power Factor:</b>	>0.96
<b>Ingress Protection Rating</b>	IP66
<b>Impact Rating</b>	IK11+
<b>Certification</b>	RCM

## ORDER CODES

Model	CCT	DIMENSION (MM)	LUMEN	Weight (kg)
<b>IQL-XLX75G3</b>	2700K/4000K/5000K	312 x 258 x 53	12000Lm	2.1
<b>IQL-XLX150G3</b>	2700K/4000K/5000K	362 x 309 x 53	24000Lm	3.38
<b>IQL-XLX200G3-4K</b>	4000K	413 x 309 x 53	32000Lm	3.72
<b>IQL-XLX300G3</b>	2700K/4000K/5000K	437 x 411 x 61	48000Lm	5.8
<b>IQL-XLX-600G3-5K</b>	2700K/4000K/5000K	437 x 411 x 61	48000Lm	5.8

Technical Data sheets available on request. Model appearance may vary. | September 2025 specifications are subject to change without prior notice.